

Sow The Seeds - Dry Erase Vinyl

Technical Data Sheet

Best Application	Dry Erase Writing Attracts Magnets
Color	White
Surface Finish	Mid High Gloss
Composition	PET with Polyester/ Non Woven backing
Width & Weight	48" width (1.22m) 54 oz / sq yd or 24 oz / lin ft (1831 g/m ²)
Roll Length	50ft (15.24m)
Warranty	10 Years
Base Film Weight	51.25 oz / sq yd (1738 g/m ²)
Backing Weight	1.80 oz / sq yd (61 g/m ²)
Top Film Weight	0.95 oz / sq yd (32.21 g/m ²)
Backing	100% Polyester
Laminate Thickness	1 mil
Total Thickness	30 mils
Flame Resistance	Class A (ASTM E-84)
Tensile Strength	275 x 208 lbs (ASTM D 5034)
Tear Strength	11.8 x 7.2 lbs (ASTM D 2261)
Solvent Resistance	1,000 Double rubs w/ MEK (ASTM D 4752)
Colorfastness	Class 4.5 – 5 at 200 AFU (AATCC 16E)
Abrasion Resistance	20,000 Double Rubs / Wyzenbeek (ASTM D 3597)

Note: For best results, rare earth or Neodymium magnets are recommended for Sow The Seeds.