



Not to Scale – July 2018

WOOD FENCING NOTES:

1. POST INSTALLATION SHALL BE SET IN CONCRETE AS PER DETAIL 2.1.
2. SPACES BETWEEN LINE POSTS SHALL BE UNIFORM AND SHALL NOT EXCEED 3.0 METRES MEASURED PARALLEL TO GROUND SURFACE.
3. CRACKS IN POSTS OR BOARDS 6-12mm IN WIDTH ARE TO BE RE-STAINED WITH FENCE STAIN ENSURING STAIN PENETRATES CORE WOOD.
4. BOARD SPACING SHALL BE TIGHT ENSURING SPACING BETWEEN BOARDS DOES NOT EXCEED 10mm WHEN BOARDS ARE DRY.
5. POSTS AND ANY WOOD IN CONTACT WITH THE GROUND TO BE PRESSURE TREATED AS PER 2.3.1. THE CITY OF LEDUC CONSTRUCTION SPECIFICATIONS.
6. ALL TIMBER POSTS AND BEAMS TO BE PRESSURE TREATED PINE OR FIR, ROUGH SAWN TIMBER PAINTED WITH TWO COATS SOLID WOOD STAIN ON BOTH SIDES PRIOR TO INSTALLATION OF STRINGERS AND FENCE BOARDS.
7. TOUCH UP STAIN TO BE APPLIED AFTER CONSTRUCTION TO ANY BOARDS WHERE STAIN HAS BEEN REMOVED, I.E. NAIL HOLES, FADED, SEE THOURH, ETC.
8. NAILER STRIPS TO BE FASTENED TO POST.
9. BOTTOM STRINGER SHALL BE 50-100mm ABOVE FINISHED GRADE AND NO TURF MAY CONTACT THE STINGER.
10. ALL LUMBER SHALL BE CLEAN, #1, CONSTRUCTION GRADE PINE, FIR OR SPRUCE MEMBERS, FINISHED AS PER THE DETAILS UNLESS OTHERWISE SPECIFIED.
11. ALL LUMBER SHALL BE STRAIGHT, SOUND AND FREE OF SPLINTS, WARPS, CRACKS, LARGE KNOTS AND OTHER DEFECTS.
12. ALL COLORS AND TYPE OF STAIN ARE AS PER THE DETAILS AND TO BE APPLIED AS PER MANUFACTURER'S SPECIFICATION AND ARE TO BE SUBMITTED TO THE LANDSCAPE ARCHITECT FOR APPROVAL PRIOR TO PROCEEDING.
13. ALL WOOD TO BE PRE-STAINED WITH SOLID STAIN 'TYPE AND COLOUR 'MUSHROOM FIELDS'.
14. ALL DIMENSIONS ARE IN MILLIMETERS (mm) UNLESS OTHERWISE NOTED.
15. ENSURE THAT FRONT OF POST IS 1.5 METERS FROM GASLINE.
16. ALL WOOD SCREEN FENCES TO BE PLACED 150mm. INSIDE PRIVATE PROPERTY.
17. ALL HARDWARE TO BE GALVANIZED.
18. PRESSURE TREATED POSTS TO BE TREATED WITH A SOLUTION OF PENTACHLOROPHENOL AND PETROLEUM TO CSA-080.
19. NAILS TO BE 89mm ARDOX COATED FOR STRINGERS TO POSTS AND 57mm ARDOX COATED FOR BOARDS (3 PER BOARD).
20. CONTRACTOR TO CALL ALBERTA FIRST CALL AT 1-800-242-3447 TO HAVE EXISTING UTILITIES LOCATED PRIOR TO START OF ANY CONSTRUCTION.
21. THIS DRAWING TO BE READ IN CONJUNCTION WITH THE WRITTEN SPECIFICATIONS, DRAWINGS AND DETAILS FOR THE PROJECT.